

## AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

1. (Currently Amended) A myotherapy massage device for the treatment of lower back ~~myofesical~~ myofascial pains, the device comprising:

a stationary base;

two laterally spaced massage heads, with each massage head having vibration means, said massage heads being operatively connected to said base and protruding vertically from said base;

a means for allowing a user of the device to selectively position[[ing]] the massage heads vertically relative to one another and relative to said base; and

a means for positioning the massage heads laterally relative to one another;

2. (Original) The device according to Claim 1, wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises

a tube having a bottom end, and a top end;

a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap; and

wherein the vibration means is disposed within the motor housing.

3. (Currently Amended) ~~The device according to claim 2,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises:

a tube having a bottom end, and a top end;

a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap; and

wherein the vibration means is disposed within the motor housing;

and

the massage device further comprising a retention plate disposed between the top and bottom ends of the tube wherein the top cap contacts and rests upon the retention plate, thereby creating top and bottom spaces within the motor housing such that the top space adjacent the top cap is smaller than the bottom space adjacent the bottom cap.

4. (Currently Amended) ~~The device according to claim 3,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises:

a tube having a bottom end, and a top end;

a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap; and

wherein the vibration means is disposed within the motor housing;

the device further comprising a retention plate disposed between the top and bottom ends of the tube wherein the top cap contacts and rests upon the retention plate, thereby creating top and bottom spaces within the motor housing such that the top space adjacent the top cap is smaller than the bottom space adjacent the bottom cap; and

wherein the vibration means comprises a motor, which turns an asymmetric weight thereby producing vibration.

5. (Currently Amended) ~~The device according to claim 4,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another; wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises:

a tube having a bottom end, and a top end;

a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap;

wherein the vibration means is disposed within the motor housing;

the device further comprising a retention plate disposed between the top and bottom ends of the tube wherein the top cap contacts and rests upon the retention plate, thereby creating top and bottom spaces within the motor housing such that the top space adjacent the top cap is smaller than the bottom space adjacent the bottom cap;

wherein the vibration means comprises a motor which turns an asymmetric weight thereby producing vibration; and

wherein the motor is disposed in the bottom space and attached to the retention plate and the weight is permitted free movement in the top space.

6. (Original) The device according to claim 2, wherein the top cap has a convex top surface.

7. (Original) The device according to claim 2, further comprising a means for heating the top cap.

8. (Original) The device according to Claim 7, wherein the means for heating the top cap is taken from the group consisting of heating coils, infrared radiation, resistance wires, and resistance wire tape disposed within the top cap and in contact thereto for conducting heat therethrough.

9. (Original) The device according to Claim 7, wherein the top cap is composed of a heat conducting material.

10. (Currently Amended) ~~The device according to Claim 2,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises:

a tube having a bottom end, and a top end;

a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap;

wherein the vibration means is disposed within the motor housing;

and

said massage device further comprising a coil compression spring disposed in the motor housing between the bottom cap and the top cap thereby cushioning the vibration means such that the vibration of the massage head is dampened with respect to the motor housing and amplified with respect to the top cap.

11. (Currently Amended) ~~The device according to Claim 3,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another; wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises:

a tube having a bottom end, and a top end;

a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap; and

wherein the vibration means is disposed within the motor housing;

the massage device further comprising a retention plate disposed between the top and bottom ends of the tube wherein the top cap contacts and rests upon the retention plate, thereby creating top and bottom spaces within the motor housing such that the top space adjacent the top cap is smaller than the bottom space adjacent the bottom cap; and

said massage device further comprising a coil compression spring disposed in the motor housing between the bottom cap and the retention plate thereby cushioning the vibration means such that the vibration of the massage head is dampened with respect to the motor housing.

12. (Currently Amended) ~~The device according to Claim 2,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises:

a tube having a bottom end, and a top end;

a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap;

wherein the vibration means is disposed within the motor housing; and  
said massage device further comprising an edge circumnavigating the tube adjacent the bottom end of the tube such that some length of tube extends therebelow.

13. (Currently Amended) ~~The device according to Claim 1,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein the means for positioning the massage heads laterally relative to one another comprises an apparatus having two opposing base assemblies slidably connected to each other by two guide rods, wherein each base assembly comprises two opposing bases having the means for positioning the massage heads vertically

relative to one another disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod.

14. (Currently Amended) ~~The device according to Claim 13,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein the means for positioning the massage heads laterally relative to one another comprises an apparatus having two opposing base assemblies slidably connected to each other by two guide rods, wherein each base assembly comprises two opposing bases having the means for positioning the massage heads vertically relative to one another disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod; and

said massage device further comprising means for restricting the movement of the base assemblies relative to the guide rods.

15. (Currently Amended) ~~The device according to Claim 13,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein the means for positioning the massage heads laterally relative to one another comprises an apparatus having two opposing base assemblies slidably connected to each other by two guide rods, wherein each base assembly comprises

two opposing bases having the means for positioning the massage heads vertically relative to one another disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod; and

wherein each guide further comprises a perpendicular threaded second opening, bisecting the first opening, for receiving a knob having a screw extension thereon which can be tightened to secure the guide rod in place.

16. (Currently Amended) ~~The device according to Claim 1,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;

wherein the means for positioning each massage head vertically comprises:

a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;



a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft.

17. (Currently Amended) ~~The device according to claim 16,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;

wherein the means for positioning each massage head vertically comprises:

a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and

wherein the crankshaft has a means for rotating the crankshaft disposed on the first end of the crankshaft.

18. (Currently Amended) ~~The device according to claim 16,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;

wherein the means for positioning each massage head vertically comprises:

a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm; the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough;

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and

said massage device further comprising a bend in the lift arm.

19. (Currently Amended) ~~The device according to claim 16,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;

wherein the means for positioning each massage head vertically comprises:

a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough;

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and

wherein the second end of the lift arm comprises a U-shaped extension such that the pivot axis assembly fits between two legs of the U-shaped extension.

20. (Currently Amended) ~~The device according to Claim 19,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein the means for positioning each massage head vertically comprises:

a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;  
a first spacer block attached to and disposed between the two opposing bases  
and having a threaded opening for receiving a first end of the crank shaft  
therethrough;

a second spacer block attached to and disposed between the two opposing  
bases and having a threaded opening therein for receiving a second end of the  
crankshaft;

wherein the second end of the lift arm comprises a U-shaped extension such  
that the pivot axis assembly fits between two legs of the U-shaped extension; and

wherein the two legs of the U- shaped extension extend past the pivot axis.

21. (Original) The device according to Claim 1, further comprising a controller for modulating the vibration frequency.

22. (Original) The device according to Claim 1, wherein the vibration means operates at a vibration frequency

- (i) greater than about 90 Hz, and
- (ii) less than about 110 Hz.

23. (Currently Amended) The device according to Claim 1, wherein the vibration means operates at a vibration frequency of about 100 [[Å5]] Hz.

24. (cancelled)

25. (cancelled)

26. (Currently Amended) A myotherapy massage device for the treatment of lower back ~~myofesial~~ myofascial pains, the device comprising:

two laterally spaced massage heads,

wherein each massage head has a motor housing enclosing a vibration means,

the motor housing has a tube having bottom and top ends,  
a bottom cap disposed on the bottom end of the motor housing, and  
a top cap disposed on the top end of the motor housing opposite the  
bottom cap;

a means for positioning the massage heads vertically relative to one  
another; and

a means for positioning the massage heads laterally relative to one another.

27. (Currently Amended) ~~The device according to Claim 26,~~ A myotherapy  
massage device for the treatment of lower back myofascial pains, the device  
comprising:

two laterally spaced massage heads, wherein each massage head has a motor  
housing enclosing a vibration means, the motor housing has a tube having bottom  
and top ends,

a bottom cap disposed on the bottom end of the motor housing, and

a top cap disposed on the top end of the motor housing opposite the bottom  
cap;

a means for positioning the massage heads vertically relative to one  
another;

a means for positioning the massage heads laterally relative to one another;

wherein the means for positioning the massage heads laterally comprises an  
apparatus having two opposing base assemblies slidably connected to one another  
by two guide rods, wherein each base assembly comprises two opposing bases  
having the means for positioning the massage heads vertically disposed between  
the bases, and a guide disposed on each base having a first opening therethrough  
for slidably receiving a guide rod.

28. (Currently Amended) ~~The device according to Claim 27,~~ A myotherapy  
massage device for the treatment of lower back myofascial pains, the device  
comprising:

two laterally spaced massage heads, wherein each massage head has a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and  
a top cap disposed on the top end of the motor housing opposite the bottom cap;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein the means for positioning the massage heads laterally comprises an apparatus having two opposing base assemblies slidably connected to one another by two guide rods, wherein each base assembly comprises two opposing bases having the means for positioning the massage heads vertically disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod; and

wherein the means for positioning each massage head vertically comprises:  
a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crankshaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft.

29. (Currently Amended) ~~The device according to Claim 28;~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, wherein each massage head has a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and  
a top cap disposed on the top end of the motor housing opposite the bottom cap;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein the means for positioning the massage heads laterally comprises an apparatus having two opposing base assemblies slidably connected to one another by two guide rods, wherein each base assembly comprises two opposing bases having the means for positioning the massage heads vertically disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod;

wherein the means for positioning each massage head vertically comprises:  
a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and



a lift axis disposed between the first and second ends of the lift arm;  
a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;  
a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;  
the crankshaft having a length, a first end, and a second end;  
a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and  
a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and  
wherein the means for attaching the massage head to the first end of the lift arm comprises an opening therethrough for receiving the motor housing of the massage head.

30. (Currently Amended) ~~The device according to claim 28,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, wherein each massage head has a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and  
a top cap disposed on the top end of the motor housing opposite the bottom cap;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;

wherein the means for positioning the massage heads laterally comprises an apparatus having two opposing base assemblies slidably connected to one another by two guide rods, wherein each base assembly comprises two opposing bases having the means for positioning the massage heads vertically disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod;

wherein the means for positioning each massage head vertically comprises:  
a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,  
a means for attaching a massage head at the first end  
a pivot axis at the second end thereof, and  
a lift axis disposed between the first and second ends of the lift arm;  
a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crankshaft having a length, a first end, and a second end;  
a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough;

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and

wherein the crankshaft has a handle for rotating the shaft disposed on the first end of the shaft.

31. (Currently Amended) ~~The device according to claim 29,~~ A myotherapy massage device for the treatment of lower back myofascial pains, the device comprising:

two laterally spaced massage heads, wherein each massage head has a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and  
a top cap disposed on the top end of the motor housing opposite the bottom cap;

a means for positioning the massage heads vertically relative to one another;

a means for positioning the massage heads laterally relative to one another;  
wherein the means for positioning the massage heads laterally comprises an apparatus having two opposing base assemblies slidably connected to one another by two guide rods, wherein each base assembly comprises two opposing bases having the means for positioning the massage heads vertically disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod;

wherein the means for positioning each massage head vertically comprises:  
a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,  
a means for attaching a massage head at the first end  
a pivot axis at the second end thereof, and  
a lift axis disposed between the first and second ends of the lift arm;  
a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second

threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crankshaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft;

wherein the means for attaching the massage head to the first end of the lift arm comprises an opening therethrough for receiving the motor housing of the massage head; and

said massage device further comprising a bend in the lift arm at the lift axis.

32. (Original) A massage device comprising:

a massage head having a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and

a top cap disposed on the top end of the motor housing opposite the bottom cap; and

a means for positioning each massage head vertically comprising a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases; the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second

threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft.

33. (Currently Amended) ~~The device according to Claim 32,~~ A massage device comprising:

a massage head having a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and

a top cap disposed on the top end of the motor housing opposite the bottom cap; and

a means for positioning each massage head vertically comprising a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases; the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and

wherein the means for attaching the massage head to the first end of the lift arm comprises an opening therethrough for receiving the motor housing of the massage head.

34. (Currently Amended) ~~The device according to claim 32,~~ A massage device comprising:

a massage head having a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and

a top cap disposed on the top end of the motor housing opposite the bottom cap; and

a means for positioning each massage head vertically comprising a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases; the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and

wherein the crankshaft has a handle for rotating the shaft disposed on the first end of the shaft.

35. (Currently Amended) ~~The device according to claim 32,~~ A massage device comprising:

a massage head having a motor housing enclosing a vibration means, the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing, and

a top cap disposed on the top end of the motor housing opposite the bottom cap; and

a means for positioning each massage head vertically comprising a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases; the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof;

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft; and

further comprising a bend in the lift arm at the lift axis.

36. (Currently Amended) A method for treating myofascial pain in the lower back of a user by relieving tension in the lower back muscles, said method comprising:

providing a massage device having a stationary base and two laterally spaced message heads, each message head having vibration means, a means for allowing the user to position[[ing]] the message heads vertically relative to one another and relative to the base, and a means for positioning the message heads laterally relative to one another;

placing the massage device on a sturdy flat surface;

placing the back on the device such that each message head comes into contact with the opposite sides of the lower back thereby applying pressure to the areas of contact

adjusting each message head's relative position; and

applying vibration to the desired locations of the lower back.

37. (Original) The method of claim 36, wherein the areas of contact are the outer sides of the muscles that run along both sides of the spine.



38. (Original) The method of claim 36, wherein the vibration is applied for about one to two minutes.

39. (Original) The method of claim 36, wherein the massage head has a means for heating the areas of contact.

40. (Original) The method of claim 39, wherein the vibration and heat are applied for about one to two minutes.